

# 舗装面積計算書

池田一丁目 補助

| 断面位置         | 距離       | 表層工(再生密粒As)㎡ |                  | 縦骨安定処理工(t=10cm)㎡ |         | 掘削工(t=10cm)㎡ |         | 不陸整正工(t=3cm)㎡ |         | 舗装版破砕(As)t=5cm |         | 摘 要              |
|--------------|----------|--------------|------------------|------------------|---------|--------------|---------|---------------|---------|----------------|---------|------------------|
| 自 B.P        |          | 6.80         |                  | 6.80             |         | 6.80         |         | 6.80          |         | 6.80           |         | ○ 舗装版切断 (As)     |
| 至 No. 1      | 20.00    | 5.50         | 123.0            | 5.50             | 123.0   | 5.50         | 123.0   | 5.50          | 123.0   | 5.50           | 123.0   | = 16.9㎡          |
| 自 No. 1      |          | 5.50         |                  | 5.50             |         | 5.50         |         | 5.50          |         | 5.50           |         | ○ 舗装版切断 (Co)     |
| 至 No. 2      | 20.00    | 5.50         | 110.0            | 5.50             | 110.0   | 5.50         | 110.0   | 5.50          | 110.0   | 5.50           | 110.0   | = ㎡              |
| 自 No. 2      |          | 5.50         |                  | 5.50             |         | 5.50         |         | 5.50          |         | 5.50           |         | ○ アスファルト設置       |
| 至 No. 3      | 20.00    | 5.50         | 110.0            | 5.50             | 110.0   | 5.50         | 110.0   | 5.50          | 110.0   | 5.50           | 110.0   | = ㎡              |
| 自 No. 3      |          | 5.50         |                  | 5.50             |         | 5.50         |         | 5.50          |         | 5.50           |         | ○ ガラ処理           |
| 至 +6.5       | 6.50     | 5.50         | 35.8             | 5.50             | 35.8    | 5.50         | 35.8    | 5.50          | 35.8    | 5.50           | 35.8    | = 95.0㎡          |
| 自 +6.5       |          | 5.50         |                  | 5.50             |         | 5.50         |         | 5.50          |         | 5.50           |         | ○ 区画線            |
| 至 +9.0       | 2.50     | 6.30         | 14.8             | 6.30             | 14.8    | 6.30         | 14.8    | 6.30          | 14.8    | 6.30           | 14.8    | = 340.0          |
| 自 +9.0       |          | 6.30         |                  | 6.30             |         | 6.30         |         | 6.30          |         | 6.30           |         | ・ センターライン (黄)    |
| 至 +13.0      | 4.00     | 6.60         | 25.8             | 6.60             | 25.8    | 6.60         | 25.8    | 6.60          | 25.8    | 6.60           | 25.8    | = 73.0           |
| 自 +13.0      |          | 6.60         |                  | 6.60             |         | 6.60         |         | 6.60          |         | 6.60           |         | ・ 外側線 (白)        |
| 至 No. 4      | 7.00     | 5.30         | 41.7             | 5.30             | 41.7    | 5.30         | 41.7    | 5.30          | 41.7    | 5.30           | 41.7    | = 20.9           |
| 自 No. 4      |          | 5.30         |                  | 5.30             |         | 5.30         |         | 5.30          |         | 5.30           |         | ・ 横断歩道           |
| 至 No. 5      | 20.00    | 5.30         | 106.0            | 5.30             | 106.0   | 5.30         | 106.0   | 5.30          | 106.0   | 5.30           | 106.0   | = 11.1           |
| 自 No. 5      |          | 5.30         |                  | 5.30             |         | 5.30         |         | 5.30          |         | 5.30           |         | ・ 停止線            |
| 至 +6.8       | 6.80     | 5.30         | 36.0             | 5.30             | 36.0    | 5.30         | 36.0    | 5.30          | 36.0    | 5.30           | 36.0    | = 92.0           |
| 自 +6.8       |          | 5.30         |                  | 5.30             |         | 5.30         |         | 5.30          |         | 5.30           |         | ・ 文字 (ダイヤ)       |
| 至 No. 6      | 13.20    | 5.30         | 70.0             | 5.30             | 70.0    | 5.30         | 70.0    | 5.30          | 70.0    | 5.30           | 70.0    | = 18.3           |
| 自 No. 6      |          | 5.30         |                  | 5.30             |         | 5.30         |         | 5.30          |         | 5.30           |         | ・ 消火栓周り区画線       |
| 至 No. 7      | 20.00    | 5.30         | 106.0            | 5.30             | 106.0   | 5.30         | 106.0   | 5.30          | 106.0   | 5.30           | 106.0   | = 2.8㎡           |
| 自 No. 7      |          | 5.30         |                  | 5.30             |         | 5.30         |         | 5.30          |         | 5.30           |         | 計 558.1㎡         |
| 至 +4.8       | 4.80     | 5.30         | 25.4             | 5.30             | 25.4    | 5.30         | 25.4    | 5.30          | 25.4    | 5.30           | 25.4    | ○ 鉄蓋調整 (φ700)    |
| 自 +4.8       |          | 5.30         |                  | 5.30             |         | 5.30         |         | 5.30          |         | 5.30           |         | (φ450)           |
| 至 No. 8      | 15.20    | 5.40         | 81.3             | 5.40             | 81.3    | 5.40         | 81.3    | 5.40          | 81.3    | 5.40           | 81.3    | 箇所               |
| 自 No. 8      |          | 5.40         |                  | 5.40             |         | 5.40         |         | 5.40          |         | 5.40           |         | 箇所               |
| 至 No. 9      | 20.00    | 5.30         | 107.0            | 5.30             | 107.0   | 5.30         | 107.0   | 5.30          | 107.0   | 5.30           | 107.0   | ○ マンホール等控除       |
| 自 No. 9      |          | 5.30         |                  | 5.30             |         | 5.30         |         | 5.30          |         | 5.30           |         | 0.5*0.5          |
| 至 +11.9      | 11.90    | 5.40         | 63.7             | 5.40             | 63.7    | 5.40         | 63.7    | 5.40          | 63.7    | 5.40           | 63.7    | * 1 = 0.25       |
| 自 +11.9      |          | 5.40         |                  | 5.40             |         | 5.40         |         | 5.40          |         | 5.40           |         | 0.7*0.65         |
| 至 No. 10     | 8.10     | 5.40         | 43.7             | 5.40             | 43.7    | 5.40         | 43.7    | 5.40          | 43.7    | 5.40           | 43.7    | * 1 = 0.46       |
| 自 No. 10     |          | 5.40         |                  | 5.40             |         | 5.40         |         | 5.40          |         | 5.40           |         | 0.7*0.7*3.14/4   |
| 至 No. 11     | 20.00    | 5.40         | 108.0            | 5.40             | 108.0   | 5.40         | 108.0   | 5.40          | 108.0   | 5.40           | 108.0   | * 9 = 3.46       |
| 自 No. 11     |          | 5.40         |                  | 5.40             |         | 5.40         |         | 5.40          |         | 5.40           |         | 0.5*0.6          |
| 至 No. 12     | 20.00    | 5.40         | 108.0            | 5.40             | 108.0   | 5.40         | 108.0   | 5.40          | 108.0   | 5.40           | 108.0   | * 1 = 0.30       |
| 自 No. 12     |          | 5.40         |                  | 5.40             |         | 5.40         |         | 5.40          |         | 5.40           |         | 計 4.5㎡           |
| 至 No. 13     | 20.00    | 5.40         | 108.0            | 5.40             | 108.0   | 5.40         | 108.0   | 5.40          | 108.0   | 5.40           | 108.0   | ○ オーパーレイ控除       |
| 自 No. 13     |          | 5.40         |                  | 5.40             |         | 5.40         |         | 5.40          |         | 5.40           |         | = ㎡              |
| 至 No. 14     | 20.00    | 5.40         | 108.0            | 5.40             | 108.0   | 5.40         | 108.0   | 5.40          | 108.0   | 5.40           | 108.0   | ○ 現況Co舗装控除       |
| 自 No. 14     |          | 5.40         |                  | 5.40             |         | 5.40         |         | 5.40          |         | 5.40           |         | = ㎡              |
| 至 +11.0      | 11.00    | 5.40         | 59.4             | 5.40             | 59.4    | 5.40         | 59.4    | 5.40          | 59.4    | 5.40           | 59.4    | ○ 視覚障害者誘導用シート設置  |
| 自 +11.0      |          | 6.60         |                  | 6.60             |         | 6.60         |         | 6.60          |         | 6.60           |         | 貼付式 樹脂製          |
| 至 No. 15     | 9.00     | 6.60         | 59.4             | 6.60             | 59.4    | 6.60         | 59.4    | 6.60          | 59.4    | 6.60           | 59.4    | = 70.0㎡          |
| 自 No. 15     |          | 6.60         |                  | 6.60             |         | 6.60         |         | 6.60          |         | 6.60           |         | 路面清掃             |
| 至 +6.7       | 6.70     | 5.60         | 40.9             | 5.60             | 40.9    | 5.60         | 40.9    | 5.60          | 40.9    | 5.60           | 40.9    | 歩道 人力 70.0m×0.3m |
| 自 +6.7       |          | 5.60         |                  | 5.60             |         | 5.60         |         | 5.60          |         | 5.60           |         | = 21.0㎡          |
| 至 +7.5       | 0.80     | 5.20         | 4.3              | 5.20             | 4.3     | 5.20         | 4.3     | 5.20          | 4.3     | 5.20           | 4.3     |                  |
| 自 +7.5       |          | 5.20         |                  | 5.20             |         | 5.20         |         | 5.20          |         | 5.20           |         |                  |
| 至 No. 16     | 12.50    | 5.10         | 64.4             | 5.10             | 64.4    | 5.10         | 64.4    | 5.10          | 64.4    | 5.10           | 64.4    |                  |
| 自 No. 16     |          | 5.10         |                  | 5.10             |         | 5.10         |         | 5.10          |         | 5.10           |         |                  |
| 至 No. 17     | 20.00    | 5.00         | 101.0            | 5.00             | 101.0   | 5.00         | 101.0   | 5.00          | 101.0   | 5.00           | 101.0   |                  |
| 自 No. 17     |          | 5.00         |                  | 5.00             |         | 5.00         |         | 5.00          |         | 5.00           |         |                  |
| 至 E.P(No.17) | 20.00    | 10.10        | 151.0            | 10.10            | 151.0   | 10.10        | 151.0   | 10.10         | 151.0   | 10.10          | 151.0   |                  |
| 自            |          |              |                  |                  |         |              |         |               |         |                |         |                  |
| 至            |          |              |                  |                  |         |              |         |               |         |                |         |                  |
| 計            | 距離 340.0 | 平均幅員 5.60    | 1,904.6          |                  | 1,904.6 |              | 1,904.6 |               | 1,904.6 |                | 1,904.6 |                  |
| 現況Co舗装控除     |          |              | 0.0              |                  | 0.0     |              | 0.0     |               | 0.0     |                | 0.0     |                  |
| オーパーレイ控除     |          |              | 0.0              |                  | 0.0     |              | 0.0     |               | 0.0     |                | 0.0     |                  |
| マンホール等控除     |          |              | 4.5              |                  | 4.5     |              | 4.5     |               | 4.5     |                | 4.5     |                  |
| 合計           |          |              | 1,900.1          |                  | 1,900.1 |              | 1,900.1 |               | 1,900.1 |                | 1,900.1 |                  |
| 改め           |          |              | 舗装復旧面積 (㎡) 1,900 |                  | 1,900   |              | 1,900   |               | 1,900   |                | 1,900   |                  |
|              |          |              |                  |                  |         |              |         |               |         | ガラ処理 (㎡) t=5cm |         |                  |
|              |          |              |                  |                  |         |              |         |               |         | As 95.0        |         |                  |

舗装数量総括表

| 路線    | 延長    | 表層工    | 悪劣安定処理工 | 掘削工    | 不陸整正工  | 舗装版直接掘削積込(㎡) |        | ガラ処理(㎡) |       | 舗装版切断工(m) |         |      | 区画線工(m) |      |      |      |     |        |         | 視覚障害者誘導用シート設置 |  | 備考 |
|-------|-------|--------|---------|--------|--------|--------------|--------|---------|-------|-----------|---------|------|---------|------|------|------|-----|--------|---------|---------------|--|----|
|       |       | 1.4≦b  | t=10cm  | t=10cm | t=3cm  | 20cm以下       | 10cm以下 | As      | As3cm | As5cm     | センターライン | 外側線  | 横断歩道    | 停止線  | ダイヤ  | 止まれ  | 消火栓 | 貼付式(m) | 路面清掃(㎡) |               |  |    |
| 池田一丁目 | 340.0 | 1900   | 1900    | 1900   | 1900   |              | 1900   | 95.0    |       | 16.9      | 340.0   | 73.0 | 20.9    | 11.1 | 92.0 | 18.3 | 2.8 | 70.0   | 21.0    |               |  |    |
| 計     |       | 1900.0 | 1900.0  | 1900.0 | 1900.0 |              | 1900.0 | 95.0    |       | 16.9      | 340.0   | 73.0 | 20.9    | 11.1 | 92.0 | 18.3 | 2.8 | 70.0   | 21.0    |               |  |    |
| 改め    |       | 1900.0 | 1900.0  | 1900.0 | 1900.0 |              | 1900.0 | 95.0    |       | 16.0      | 340.0   | 73.0 | 20.0    | 11.0 | 92.0 | 18.0 | 2.0 | 70.0   | 21.0    |               |  |    |