

3号箇所 国母七丁目 単独

断面位置								距離								表層工(再生密粒As)㎡								不陸整正工 (t=3cm) ㎡								舗装版破碎 (As) t=5cm								摘 要							
自 至	B. P. 3			8. 15			8. 15			8. 15			8. 15			8. 15			8. 15			8. 15			8. 15			8. 15			○ 舗装版切断 (As)	=	<div>7. 6</div> m														
自 至	+2. 4		2. 40	6. 00		17. 0	6. 00		17. 0	6. 00		17. 0	6. 00		17. 0	6. 00		17. 0	6. 00		17. 0	6. 00		17. 0	6. 00		17. 0	6. 00		17. 0	○ 舗装版切断 (Co)	=	<div></div> m														
自 至	+2. 4			5. 40			5. 40			5. 40			5. 40			5. 40			5. 40			5. 40			5. 40			5. 40			○ アスカーフ設置	=	<div></div> m														
自 至	+13. 5		11. 10	5. 40		59. 9	5. 40		59. 9	5. 40		59. 9	5. 40		59. 9	5. 40		59. 9	5. 40		59. 9	5. 40		59. 9	5. 40		59. 9	5. 40		59. 9	○ ガラ処理	=	<div></div> m ³														
自 至	+13. 5			5. 40			5. 40			5. 40			5. 40			5. 40			5. 40			5. 40			5. 40			5. 40			○ 区画線	=															
自 至	E. P3 (+15. 9)		2. 40	7. 60		15. 6	7. 60		15. 6	7. 60		15. 6	7. 60		15. 6	7. 60		15. 6	7. 60		15. 6	7. 60		15. 6	7. 60		15. 6	7. 60		15. 6	・ 外側線	=															
自 至																														・ センターライン	=																
自 至																														・ 文字 (直左・直右・右折)	=																
自 至																														・ 文字 (40)	=																
自 至																														・ ゼブラ	=																
自 至																														・ 停止線 (止まれ)	=																
自 至																														計	<div></div> m																
自 至																															○ 鉄蓋調整 (φ 700)		<div></div> 箇所														
自 至																														(φ 450)		<div></div> 箇所															
自 至																														○ マンホール等控除																	
自 至																														0. 16*0. 16*3. 14/4	*	=															
自 至																														0. 38*0. 38*3. 14/4	*	=															
自 至																														0. 4*0. 4*3. 14/4	*	=															
自 至																														0. 7*0. 7*3. 14/4	*	2 = 0. 77															
自 至																														0. 52*0. 52*3. 14/4	*	=															
自 至																															*	=															
自 至																														計	<div>0. 8</div> ㎡																
自 至																															○ オーバーレイ控除	=	<div></div> ㎡														
自 至																																															
自 至																															○ 現況Co舗装控除	=	<div></div> ㎡														
自 至																																															
自 至																																															
自 至																																															
自 至																																															
自 至																																															
自 至																																															
自 至																																															
自 至																																															
自 至																																															
自 至																																															
自 至																																															
自 至																																															
自 至																																															
自 至																																															
自 至																																															

4号箇所 国母七丁目 单独

断面位置								距離		表層工(再生密粒As) m ²		不陸整正工 (t=3cm) m ²		舗装版破砕 (As) t=3cm		摘 要	
自 至	B. P4 +4.5		4.50	6.30		28.4	6.30	28.4	6.30	28.4					○ 舗装版切断 (As)	=	<div>3.3</div> m
自 至	+4.5			6.30			6.30		6.30						○ 舗装版切断 (Co)	=	<div></div> m
自 至	+5.8	1.30		4.60	7.1		4.60	7.1	4.60	7.1					○ アスカーフ設置(巾20cm)	=	<div></div> m
自 至	+5.8 +6.2		0.40	4.60		1.8	4.60	1.8	3.45						○ ガラ処理	=	<div></div> m ³
自 至	+6.2 No. 1	13.80		4.40	60.7		4.40	60.7	3.25	44.9					○ 区画線	=	<div></div> m
自 至	No. 1 +17.5	17.50		4.40	77.0		4.40	77.0	3.25	56.9					・ 外側線	=	
自 至	+17.5 E. P4(+17.8)	0.30		3.70	3.30	1.1	3.70	3.30	2.55	2.15	0.7				・ センターライン	=	
自 至															・ 文字 (直左・直右・右折)	=	
自 至															・ 文字 (40)	=	
自 至															・ 停止線 W=45cm	=	2
自 至															・ 停止線 (止まれ)	=	18.3
自 至															計		<div>20.3</div> m
自 至															○ 鉄蓋調整 (φ 700)		<div></div> 箇所
自 至															(φ 450)		<div></div> 箇所
自 至															○ マンホール等控除		
自 至									0.48*0.48*3.14/4	*	2 = 0.36						
自 至									0.38*0.38*3.14/4	*	1 = 0.11						
自 至									0.7*0.7*3.14/4	*	=						
自 至									0.5*0.5	*	1 = 0.25						
自 至									0.55*0.5	*	=						
自 至									0.4*0.5	*	=						
自 至															計		<div>0.7</div> m ²
自 至															○ オーバーレイ控除	=	<div></div> m ²
自 至																	
自 至															○ 現況Co舗装控除	=	<div></div> m ²
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	
自 至																	

単独

路線番号	延長	表層工	路盤工	不陸整正工 (t=3cm)	舗装版直接掘削積込 (㎡)		ガラ処理 (㎡)	舗装版切断工 (m)		区画線工 (m)						備考
		1.4≦b			20cm以下	10cm以下	As	Co5cm	As5cm	外側線	センターライン	文字・記号	ゼブラ・停止線	ダイヤモンド	破線 (W=30)	
3号箇所	15.9	91		91		91	4.6		7.6							
4号箇所	37.8	175		175		138	6.9		3.3			18.3	2.0			
計		266.0		266.0		222.0	11.5		10.9			18.3	2.0			
改め		260		260		220	11		10			18	2			

合計

境界壁分を控除

路線番号	延長	表層工	路盤工	不陸整正工 (t=3cm)	舗装版直接掘削積込 (㎡)		ガラ処理 (㎡)	舗装版切断工 (m)		区画線工 (m)					
		1.4≦b			20cm以下	10cm以下	As	Co5cm	As5cm	外側線	センターライン	文字・記号	ゼブラ・停止線	ダイヤモンド	破線 (W=30)
	53.7	260		260		220	11		10			18	2.0		

・ 本 管 土 工 計 算 書

工 事 名 : 道路維持工事 (R4-5) 排水管設置


単独

項 目	種 別	計 算 式	数 量
機 械 埋 戻	V5	RC40-0 G2 * B * ΣL 0.15 * 1.00 * 3.00	0.5
管上30cm 機 械 埋 戻	V7	クッション用砂 E * ΣL 0.270 * 3.00	0.8
砂基礎 機 械 埋 戻		基礎厚 * B * 管体延長 0.100 * 1.00 * 3.00	0.3

項 目	a	a'	c	d	管断面積	e	E
舗 装 道				H-a-c-e	内径 : 0.155 管厚 : 0.005	0.2+0.005*2 +0.155+0.1	1*(0.4-0.1) -0.03
数 量					0.03	0.40	0.270

(舗装道・機械掘削)

A型



a : 舗装版復旧厚
c : 碎石類厚
d : 発生土, 埋戻用材厚
e : 基礎厚+管上15cm埋戻厚
H : 掘削深